

Technical drawing of a chair (BOCCOLA Ø20) showing side and front views with dimensions.

Side View Dimensions:

- Overall height: 100
- Seat height: 25
- Seat width: 16
- Seat depth: 18
- Backrest height: 66
- Backrest width: 10
- Backrest depth: 15
- Base width: 7
- Base depth: 25

Front View Dimensions:

- Overall width: 20
- Seat width: 16
- Seat depth: 18
- Backrest width: 10
- Backrest depth: 15
- Base width: 7
- Base depth: 25

BOCCOLA Ø20

[illegible]

Technical drawing of a lampshade (BOCCOLA Ø20) showing dimensions in cm.

Side View Dimensions:

- Height: 100
- Top Width: 18
- Bottom Width: 16
- Top Flange Width: 5
- Top Flange Height: 4
- Bottom Flange Width: 8
- Bottom Flange Height: 8

Top View Dimensions:

- Length: 18
- Width: 16

Detail View Dimensions:

- Top Flange Width: 5
- Top Flange Height: 4
- Bottom Flange Width: 8
- Bottom Flange Height: 8

BOCCOLA Ø20

[illegible]

MANICOTTO DI COMPENSAZIONE
DYWIDAG

41

6.5

6

12

10

2

56

100

25

7

FORO Ø60

57

55

FORO Ø60

PIATTO DI UNIONE ELEMENTI
VEDI PARTICOLARE

17

17

18

18

MANICOTTO DI COMPENSAZIONE
DYWIDAG

PART. DISTANZIAMENTO BARRIERE

BARRA DYWIDAG Ø20

BULLONI M20 x 50 x 8.8

PIATTO DI UNIONE

BOCCHILLA Ø20
L=6

4.3

20

6.5

6

20

6

17

17

1

1

18


18

TUBO IN PVC Ø15 mm
L=100 cm


IL TUBO IN PVC, POGGIATO O INCOLLATO NELL' INCAVO DELLA TESTATA FEMMINA DURANTE LA FASE DI POSA DELLA BARRIERA ADIACENTE, EVITERA' IL CONTATTO TRA LE TESTATE E GARANTIRA' LA LIBERA DILATAZIONE TERMICA A CIASCUN ELEMENTO

Technical drawing of a mechanical part, showing a side view (top) and a front view (bottom). The side view shows a rectangular block with a total length of 28 and a width of 5. The front view shows a rectangular block with a total width of 7.5 and a height of 3.75. The front view also shows two circular features, each with a diameter of 2.35, and a central rectangular feature with a width of 2.6 and a height of 2.35. The side view shows two vertical lines, each with a height of 18, and a central rectangular feature with a width of 5 and a height of 18.


PROSPETTO
scala 1:10



VISTA A-A
scala 1:10






SEZIONE B-B
scala 1:10





SEZIONE C-C
scala 1:10



SEZIONE SULLA TESTATA
scala 1:5



SEZIONE IN MEZZERIA
scala 1:5







⑥ 2-2Ø12 L=50
50

⑩ 2Ø12 L=100
100

POSIZIONE	N	Ø	L. unit.	L. tot.	Kg unit.	NOTE
①	1	20	597	597	14.72	DYWIDAG
②	2	12	552	1104	9.80	
③	2	12	593	1186	10.53	
④	2	16	593	1186	18.72	
⑤	3	12	593	1779	15.80	
⑥	4	12	50	200	1.78	
⑦	3	10	305	915	5.65	
⑦bis	1	10	287	287	1.77	
⑧	27	10	336	9072	55.97	
⑨	2	12	557	1114	9.89	
⑩	2	12	100	200	1.78	
⑪	2					Boccole Ø20
⑫	4					PIASTRE 150x100x10 zincate ø12 L=100
TOTALE	2-10				131.69	

PARTICOLARE SULL'ASOLA DI FISSAGGIO
scala 1:5



NOTA: OBBLIGATORIO L'USO DI DISTANZIATORI IN PLASTICA PER COPRIFERRO MIN. 20 mm